



HOW TO WATERPROOF YOUR SHOWER

PREPARATION



1 You will need: safety equipment, a broom for cleaning, a drill with paddle mixer, approximately 2L of water, a block brush and 5kg TAL SUREPROOF SHOWER




2 Ensure the moisture content of the shower surface area is less than 8%



3 Fill any holes or surface defects with a suitable quick-setting repair compound



4 Ensure the surface is integrally sound, clean and free from any contamination, such as dust, dirt, waxes, bituminous compounds and organic or fungal growth




PRIMING THE SURFACE

5 You do not need to prime a rendered or screeded surface that is clean, dry and free from contaminants



6 Dry walls and highly porous surfaces


Prime dry walls and highly porous surfaces with a coat of neat TAL FLOOR PRIMER



7 Wooden surfaces

Prime wooden and metal surfaces with a TAL KEYCOAT and TAL KEYMIX slurry

MIXING




8 Pour approx. 2L of water into a clean bucket



9 Using a mechanical mixer, mix while adding the TAL SUREPROOF SHOWER powder




10 Mix for at least five minutes until the liquid has a smooth, lump free, paint like consistency.




11 Let it stand for 3 minutes – then stir again


APPLICATION




12 Apply the **first coat** to the clean, dry surface with a block brush in a vertical direction.



13 Check that the **first coat** is touch dry before applying the second coat. (1-2 hours)



14 Apply the **second coat** in a horizontal direction to the first coat to ensure complete coverage



15 Waterproof to a minimum 100mm above the shower rose



16 **Upstairs showers only:** Use a reinforcing membrane (200mm wide) in internal corners, interfaces, around tap and rose plumbing fittings as well as drains



17 Allow TAL SUREPROOF SHOWER to dry completely for 24-36 hours

TILING



18 Tile the shower with a quick or rapid setting adhesive using TAL BOND as a total water replacement. Then use TAL grout mixed with TAL BOND to finish the installation



TAL SUREPROOF SHOWER is fully compatible with all TAL tile adhesives and grout.



Watch this step by step video on our Youtube channel

TAL FREE TECHNICAL ADVICE CENTRE: 0860 000 TAL (825) • taltech@tal.co.za • www.tal.co.za

Johannesburg: 011 206 9700 Cape Town: 021 386 1810 Durban: 031 579 2263