

DATA SHEET

PRIMER AGGREGATE

Revision Date
DECEMBER 2016



Graded Silica Sand for Mechanical Keying and Slip Resistance

Description

TAL Primer Aggregate is high-quality well-graded silica sand.

It provides a mechanical key for resin flooring systems as well as cementitious screeds/toppings/underlayments.

TAL Primer Aggregate is also used in conjunction with TAL resin flooring and coating systems to provide a slip resistant finish.

Available in Fine (SQ1), Medium (SQ2) and Coarse (SQ3).

Note : This product is designed for the above-mentioned application only. TAL will not be liable for misuse or adulteration of the product.

Advantages

- Provides a mechanical key for cementitious screeds/toppings/underlayments and resin flooring
- Provides a non-slip finish to resin flooring coatings/coverings
- Dust free
- Uniform size and consistency
- Low resin absorption

Precautions

- Do not apply onto a coating that has exceeded its open time (ie dry epoxy or urethane).
- Should the **TAL Primer Aggregate** become damp/wet, allow to dry out completely before use.

Packaging

TAL Primer Aggregate SQ1 – 40kg bags

TAL Primer Aggregate SQ2 – 40kg bags

TAL Primer Aggregate SQ3 – 40kg bags

Theoretical Coverage

	30% Broadcast	100% Broadcast (FULL BLIND)
SQ1	300 g/m ²	1000 g/m ²
SQ2	250 g/m ²	750 g/m ²
SQ3	200 g/m ²	650 g/m ²

Shelf Life & Storage

Indefinite when stored in dry conditions. Never store directly on a concrete floor. Protect from damp and rain.

Installation / Health & Safety

This product is for industrial use only by trained operatives. It is potentially hazardous if not used correctly.

Please refer to the Method Statement (MS) prior to the purchase and use of this product.

TAL Technical Advice Centre

For advice or a detailed Materials and Methods Specification contact the TAL Technical Advice Centre on 0860 000 TAL(825), or e-mail taltech@tal.co.za.

Branches : Gauteng (011) 206-9700;

Cape (021) 386-1810; Natal (031) 579-2263

Important Notice:

TAL believes the information on this sheet to be correct – but does not guarantee its accuracy or completeness. Conduct your own tests of this product to determine its suitability for intended use. User assumes all risks and liability during testing and use of this product. In special cases, obtain professional advice. The only obligation of TAL shall be to replace any of this product proved to be defective in material. TAL shall not be liable for any injury, loss or damage, direct or consequential, relating to the use or inability to use this product. Except as expressly provided above, all products sold and samples furnished without any warranty of merchantability or any other warranty, express or implied. TAL reserves the right to change the information on this datasheet. Please contact the TAL Technical Advice Centre on taltech@tal.co.za, or 0860 000 825 to ensure you have the latest version.