

DATA SHEET

PRO-TAC

Issue Date
APRIL 2019



Solvent-Free Modified Acrylic Adhesive

Description

TAL Pro-Tac is a solvent free, modified acrylic based adhesive, suitable for the installation of carpets and carpet tiles where repositionability or removability is important.

TAL Pro-Tac is suitable for application onto concrete, screed, toppings, underlayment compounds, render, tiles, wood, vinyl and metal access flooring.

TAL Pro-Tac is **NOT** suitable for adhering carpeting that has been coated with a rubber or bitumen based wear-under layment.

Note : This product is designed for the above-mentioned application only. TAL will not be liable for misuse or adulteration of the product.

Laboratory Test Data

Type	Modified Acrylic Emulsion
Colour	Creamy White
Flash Off Time*	± 30 Minutes
Open Time*	Permanently tacky in dust-free areas
Solids Content	60 ± 2%
Viscosity (Brookfield)	8000 – 12000 cPs (RVT 6/20/25°C)
Specific Gravity	1.00 ± 0.02
pH	7 – 9
Temperature Application Range	10°C - 30°C
Coverage	1.5mm Serrated Trowel : ± 6m ² /ℓ Paint Roller : ± 7m ² /ℓ
Cleaning	Water when wet Solvent when dry

*At 23°C and 50% relative humidity.

Note: The above data was obtained under Laboratory conditions using freshly manufactured material. Actual results in the field will vary as a result of factors such as Ambient Temperatures, Site Conditions, etc.

Packaging

TAL Pro-Tac is available 20ℓ plastic containers.

Approximate Coverage

1.5mm Serrated Trowel : ± 6m² / ℓ

Paint Roller : ± 7m² / ℓ

NB : Actual coverages will be determined by site conditions, workmanship, etc.

Storage & Shelf Life :

Ensure container is tightly sealed and packaging is secure and upright.

Secure product when transporting to prevent accidental spillage.

When stored in original sealed packaging in dry internal conditions between 10°C and 30°C and out of direct sunlight the product has a shelf life of 6 months from date of manufacture.

Never store directly on a concrete floor.

Installation / Health & Safety

This product is for industrial use only by trained operatives. It is potentially hazardous if not used correctly.

Please refer to the Method Statement (MS) and Material Safety Data Sheet (MSDS) prior to the purchase and use of this product.

TAL Technical Advice Centre

For advice or a detailed Materials and Methods Specification contact the TAL Technical Advice Centre on 0860 000 TAL(825), or e-mail taltech@tal.co.za.

Branches : Gauteng (011) 206-9700;

Cape (021) 386-1810; Natal (031) 579-2263

Important Notice:

TAL believes the information on this sheet to be correct – but does not guarantee its accuracy or completeness. Conduct your own tests of this product to determine its suitability for intended use. User assumes all risks and liability during testing and use of this product. In special cases, obtain professional advice. The only obligation of TAL shall be to replace any of this product proved to be defective in material. TAL shall not be liable for any injury, loss or damage, direct or consequential, relating to the use or inability to use this product. Except as expressly provided above, all products sold and samples furnished without any warranty of merchantability or any other warranty, express or implied. TAL reserves the right to change the information on this datasheet. Please contact the TAL Technical Advice Centre on taltech@tal.co.za, or 0860 000 825 to ensure you have the latest version.