

TASKI® Jontec Technique

Floor sealer

Description

Semi permanent floor sealer for the basic treatment of most types of porous hard floors. Specific polymers used in the product fill the pores, facilitate adhesion and help reduce the consumption of further coats of floor emulsion. By ensuring the proper adhesion, subsequent floor emulsions will show greater durability.

Key properties

- Facilitates adhesion
- Semi permanent layer
- Fills the pores
- Reduces the consumption of the floor emulsion on top

Benefits

- Ideal to use on most problematic material, floors and surfaces
- Conventional floor emulsions can be selectively removed without affecting the sealer
- Prepares the floor to ease the application of floor emulsions on porous or damaged floors
- Allows savings on application of floor emulsion
- Suitable for traditional applications with a flat mop, mop and bucket or standard polish applicators

Use instructions

Dosage:


TASKI Jontec Technique is ready to use. For detailed information regarding the dosing, please refer to the Technical Data table. Proper dosage saves costs and minimises environmental impact.

Application

Treat only stripped, thoroughly rinsed and completely dry floors. Sparingly pour the product onto the floor and evenly spread it while wet in overlapping lanes of 1-1.5m. Allow the floor to dry completely (typically 20-40 minutes). Apply a second coat on very porous floors.

Allow to dry completely and then apply further coats of your choice of Diversey Care standard floor emulsion until the desired appearance is reached.

F2h



© A.I.S.E.

TASKI[®] Jontec Technique

Floor sealer

Technical data

Platform	SKU	Description/Pack size	RTU	Appearance	pH value neat	pH value in-use	Relative density (20°C)
Standard concentrate	7513198	TASKI Jontec Technique 2 x 5 L	RTU - 100%	Milky white liquid	≈ 9	≈ 9	1.03g /cm ³

The above data is typical of production and should not be taken as specification.

Safe handling and storage information

Full guidance on the handling and disposal of this product is provided in a separate Safety Data Sheet (SDS). <https://sds.sealedair.com/>

Only for professional users/specialists. Store in original closed containers away from extremes of temperature. Do not store or use at temperatures below 5°C.

Product compatibility

Treat only deep cleaned, thoroughly rinsed and completely dry floors. Do not use on wooden floors. Apply only to completely cured (dried out) cement and armoured concrete floors.

Sealed Air Africa (Pty) Ltd

Co. Reg. no: 1997/01803/07

Cnr Nagington & Rossouw Roads,
Private Bag X037, 1422, Wadeville, Gauteng, South Africa
Tel: (011) 871 9000 Fax: (011) 871 9086

www.SealedAir.com